







*Molten Bronze* 2-3

*Elegance* 4-5

*Traditionale* 6-7

*Essentials* 8-9

*Reliant* 10

*Interconnect* 11

*U.L. 60 Minutes Rated* 12-13



# Molten Bronze

- Limited Lifetime Mechanical Warranty

## ***Standard Collection Features***

- 5-Pin Cylinder
- Weslock keyway (optional Schlage Keyway)
- Exceeds ANSI A 156.2 Grade II lock standards

- Limited 10 Year Finish Warranty

## ***Standard Collection Specifications***

- Adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Optional door thickness up to 2-1/4"

## ***Entry Handle Standard Features***

- Solid Molten Brass
- 1" Throw bolt with two hardened steel rollers prevent sawing
- Removable knob/lever prevents scratching during installation
- Heavy Duty Security Strikes with 3" screws

## ***Specifications***

- Adjusts to door thickness from 1-3/4" - 2"

### ***-Castletown/Aspen***

- Fits doors prepared with 2-1/8" top (1-5/8" optional) and 2-1/8" bottom cross holes and 1" edge hole
- 5-1/2" center to center cross hole spacing (minimum 5-1/4")

### ***-Stonebriar/Wiltshire/Tramore/ Greystone/Rockford***

- Fits doors prepared with 2-1/8" top (1-5/8" optional) and 2-1/8" bottom cross holes and 1" edge hole
- 5-1/2" minimum center to center cross hole spacing
- Interconnect feature available



ASPEN



GREYSTONE



ROCKFORD



TRAMORE



CASTLETOWN



STONEBRIAR




WILTSHIRE




DURHAM KNOB



WEXFORD KNOB



CARLOW LEVER



MONOGHAN LEVER



WATERFORD LEVER

## Knob & Lever Standard Features

- Cylindrical Door Locks
- ADA compliant levers
- Panic-Proof keylock/privacy— one turn of interior knob/lever unlocks & opens door
- Push button locking in rosette
- Solid Molten Bronze levers, knobs, and rosettes
- Removable knob/lever prevents scratching during installation

## Specifications

- Adjusts to door thickness from 1-3/8" to 1-3/4"
- Fits doors prepared with 2-1/8" cross hole & 1" edge hole

## Rosettes



Square



Premiere



Sutton

## Finishes

Style	1	2	P
Durham/Wexford Knob			
Premiere	•	*	•
Square	•	•	•
Carlow/Waterford Lever			
Premiere	•	*	•
Square	•	•	•
Monaghan Lever			
Square	•	•	•
Deadbolts			
Premiere	•	*	•
Square	•	•	•
Aspen Entry Handle	•	•	•
Castletown Entry Handle	•	*	•
Greystone Entry Handle	•	•	•
Rockford Entry Handle	•	•	•
Stonebriar Entry Handle	•	*	•
Tramore Entry Handle	•	*	•
Wiltshire Entry Handle	•	*	•



Oil Rubbed Bronze (1)



Black (2)



Weathered Pewter (P)



Premiere



Square

## Deadbolt Standard Features

- 1" Throw bolt with two hardened steel rollers prevent sawing
- Heavy Duty Security Strikes with 3" screws

## Specifications

- Fits doors prepared with 2-1/8" cross hole (1-5/8" optional) and 1" edge hole
- Adjusts to door thickness from 1-3/8" - 2"

# Elegance

- Limited Lifetime Mechanical Warranty

## Standard Collection Features

- 5-Pin Cylinder
- Weslock keyway (optional Schlage Keyway)
- Exceeds ANSI A 156.2 Grade II lock standards

- Limited Lifetime Finish Warranty

## Standard Collection Specifications

- Adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Optional door thickness up to 2-1/4"

## Entry Handle Features

- Solid Brass
- Removable knob/lever prevents scratching during installation
- 1" Throw bolt with two hardened steel rollers prevent sawing
- Interconnect feature available
- Heavy duty security strikes with 3" screws

## Specifications

- Adjusts to door thickness from 1-3/4" - 2"
- Fits doors prepared with 2-1/8" top (1-5/8" optional) and 2-1/8" bottom cross holes and 1" edge hole
- 5-1/2" center to center cross hole spacing



MANSION™



STANFORD™



PHILBROOK



WOODWARD I



WOODWARD II



Premiere

Oval

Woodward

## Deadbolt Standard Features

- 1" Throw bolt with two hardened steel rollers prevent sawing
- Heavy duty security strikes with 3" screws

## Specifications

- Adjusts to door thickness from 1-3/8" - 2"
- Oval/Woodward
- Fits doors prepared with 2-1/8" cross hole and 1" edge hole
- Premiere
- Fits doors prepared with 2-1/8" cross hole (1-5/8" optional) and 1" edge hole.




JULIENNE KNOB  
PREMIERE



JULIENNE KNOB  
OVAL



IMPRESA™ KNOB  
WOODWARD



LEGACY LEVER  
PREMIERE



BORDEAU LEVER  
PREMIERE



URBANA LEVER  
WOODWARD



UTICA LEVER  
WOODWARD

### Knob & Lever Standard Features

- Cylindrical Door Locks
- Removable knob/lever prevents scratching during installation
- Panic-Proof keylock/privacy— one turn of interior knob/lever unlocks & opens door
- Push button locking in rosette
- Zinc diecasted levers and rosettes
- All brass knobs
- ADA compliant levers

### Specifications

- Fits doors prepared with 2-1/8" cross hole & 1" edge hole
- Adjusts to door thickness from 1-3/8" to 1-3/4"

### Rosettes



Premiere



Oval



Woodward

### Finishes

Style	N	1	P
Premiere			
Impresa/ Julienne Knobs	•	•	•
Bordeau/Legacy Levers	•	•	•
Oval			
Julienne Knobs	•	•	
Bordeau/Legacy Levers	•	•	
Woodward			
Impresa Knob	•	•	
Urbana/Utica Levers	•	•	
Deadbolts			
Premiere	•	•	•
Oval/Woodward	•	•	
Mansion Entry Handle	•	•	•
Stanford Entry Handle	•	•	
Phillbrook Entry Handle	•	•	•
Woodward I Entry Handle	•	•	
Woodward II Entry Handle	•	•	
  			
Satin Nickel (N)   Oil Rubbed Bronze (1)   Weathered Pewter (P)			

# Traditionale

- Limited Lifetime Mechanical Warranty
- Limited Lifetime Finish Warranty
- Limited Lifetime PVD Finish on Exterior Polished Brass

## Standard Collection Features

- 5-Pin Cylinder
- Weslock Keyway (optional Schlage Keyway)
- Exceeds ANSI A 156.2 Grade II lock standards

## Standard Collection Specifications

- Optional door thickness up to 2-1/4"



**LEXINGTON™**  
(2100 SERIES)



**LEXINGTON™**  
(1300 SERIES)



**COLONIAL™**  
(2100 SERIES)



**COLONIAL™**  
(1300 SERIES)

## Entry Handle Features

- Solid Brass
- Removable knobs/levers prevents scratching during installation
- 1" throw deadbolt with two hardened steel rollers prevent sawing
- Heavy duty security strikes with 3" screws

## Specifications

- Fits doors prepared with 2-1/8" top ( 1-5/8" optional) and 2-1/8" bottom cross hole and 1" edge hole

### 2100 Series Entry Handle

- Adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Adjusts to door thickness from 1-3/4" to 2"
- 5-1/2" center to center cross hole spacing (minimum 5-1/4")

### 1300 Series Entry Handle

- Non-adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Adjusts to door thickness form 1-3/4" to 2-1/4"
- 8" minimum center to center cross hole spacing



**MODEL 671**

**MODEL 672**



**MODEL 667**

**MODEL 668**

## Deadbolt Standard Features

- Heavy duty security strikes with 3" screws
- 1" Throw bolt with two hardened steel rollers prevent sawing
- ADA recommended, extra large interior thumbturn
- 1/4" diameter through bolt with rotating collar (671/672)
- Heat treated assembly housing screws (671/672)
- Anti-force shield (671/672)


## Specifications

- Adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Fits doors prepared with 2-1/8" cross holes and 1" edge hole
- Adjusts to door thickness from 1-3/8" - 2"





BALL



ELEGANT™



IMPRESA™



JULIENNE



SAVANNAH™

### Knob & Lever Standard Features

- Cylindrical Door Locks
- ADA compliant levers
- Removable knobs/levers prevents scratching during installation
- Pre-installed screws concealed behind snap-on rosette
- Panic-Proof Keylock/Privacy— one turn of interior knob/lever unlocks & opens door
- Push Button locking in rosette
- Zinc diecasted levers
- All brass knobs and rosettes

### Specifications

- Adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Fits doors prepared with 2-1/8" cross hole & 1" edge hole
- Adjusts to door thickness from 1-3/8" to 1-3/4"




ACCESS™




BORDEAU™



CALAIS™



LEGACY



URBANA

### Finishes

Style	A	B	D	N	1	2	P	3	6
Ball Knob	•	•						•	
Savannah™ Knob	•			•	•				
Eleganti™ Knob	•								
Impresa™ Knob	•	•	•	•	•	•	•	•	•
Julienne Knob				•	•			•	
Access™ Lever		•	•					•	
Bordeau Lever	•	•	•	•	•	•	•	•	•
Calais™ Lever	•		•	•					
Legacy Lever				•	•				
Urbana Lever				•	•				
671 Deadbolt	•	•	•	•	•		•		•
672 Deadbolt	•	•	•						
667/668 Deadbolt	•	•	•					•	
Colonial 2100/1300 Entry Handle	•								
Lexington 2100 Series Entry Handle	•	•	•	•	•	•	•		•
Lexington 1300 Series Entry Handle	•	•		•	•				











Antique Brass (A)

PVD (B)

Satin Chrome (D)

Satin Nickel (N)

Oil Rubbed Bronze (1)

Black (2)

Weathered Pewter (P)

Polished Brass (3)

Bright Chrome (6)

# Essentials

- Limited Lifetime Mechanical Warranty
- Limited 10 Year Finish Warranty
- Limited Lifetime PVD Finish on Exterior Polished Brass

## Collection Standard Features

- 5-Pin Cylinder
- Weslock Keyway (optional Schlage Keyway)

## Standard Collection Specifications

- Adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Optional door thickness up to 2-1/4"



OVAL

## Entry Handle Features

- Zinc diecasted exterior, brass stamped interior
- 1" Throw bolt with two hardened steel rollers prevent sawing
- Heavy Duty Security Strikes with 3" screws

## Specifications

- Adjusts to door thickness from 1-3/4" - 2"
- Fits doors prepared with 2-1/8" top ( 1-5/8" optional ) and 2-1/8" bottom cross hole and 1" edge hole
- 5-1/2" center to center cross hole spacing ( 5-1/4" minimum )



MODEL 371



MODEL 372

## Deadbolt Standard Features


- Heavy Duty Security Strikes with 3" screws
- 1" Throw bolt with two hardened steel rollers prevent sawing
- ADA recommended, extra large interior thumbturn

## Specifications

- Fits doors prepared with 2-1/8" ( 1-5/8" optional ) cross hole and 1" edge hole
- Adjusts to door thickness from 1-3/8" - 2"



BARRINGTON™



SONIC™



LEXINGTON™



PROVENCE










### Knob & Lever Standard Features

- Cylindrical Door Locks
- Exceeds ANSI A 156.2 Grade II lock standards
- Pre-installed screws concealed behind snap-on rosette
- Removable knobs/levers prevents scratching during installation
- Panic-Proof Keylock/Privacy— one turn of interior knob/lever unlocks & opens door
- Push button locking in rosette
- Zinc diecasted levers
- All brass knobs and rosettes
- ADA compliant levers

### Specifications

- Fits doors prepared with 2-1/8" cross hole & 7/8" or 1" edge hole
- Latch diameter is 7/8"
- For 1" edge hole, non-mortise applications requires metal sleeve
- Adjusts to door thickness from 1-3/8" to 1-3/4"

### Finishes

Style	A	B	D	N	1	2	P	3	6
Barrington™ Knob	•	•	•	•	•			•	
Sonic™ Knob	•	•	•					•	
Lexington™ Lever	•	•	•	•				•	
Provence Lever	•	•	•	•	•			•	
371/372 - Deadbolt	•	•	•	•	•	•	•		•
Oval Entry Handle		•		•	•				
        									
Antique Brass (A)   PVD (B)   Satin Chrome (D)   Satin Nickel (N)   Oil Rubbed Bronze (1)   Black (2)   Weathered Pewter (P)   Polished Brass (3)   Bright Chrome (6)									

# Reliant

- Limited 10 Year Mechanical Warranty

## Collection Features

- Exceeds ANSI Grade 3 lock standards
- Weslock Keyway (optional Schlage and Kwikset keyways)
- 5-pin cylinder
- Turn button locking in knob/lever
- Half moon spindle tubular design

- Limited 5 Year Finish Warranty

## Collection Specifications

- Adjustable latches 2-3/8" or 2-3/4" with radius faceplates and strikes
- Adjusts to door thickness from 1-3/8" to 2"
- Entry handle fits doors prepared with 2-1/8" top ( 1-5/8" optional ) and 2-1/8" bottom cross hole and 1" edge holes
- Knob/Lever fits door prepared with 2-1/8" cross hole and 1" edge hole
- Deadbolt fits door prepared with 2-1/8" ( 1-5/8" optional ) and 1" edge hole



HUDSON



BRADEN



SALEM



TULIP



BRISTOL



NEW HAVEN



SOMERSET



HILLCREST

## Finishes

Style	A	N	1	3
Hudson/Braden/Salem Knob		•	•	
Tulip Knob	•			•
New Haven/Bristol/Somerset Lever		•	•	
Deadbolt	•	•	•	•
Hillcrest Entry Handle		•	•	
   				
Antique Brass (A)    Satin Nickel (N)    Oil Rubbed Bronze (1)    Polished Brass (3)				



MODEL 267



MODEL 271



MODEL 272



# Interconnect

- Limited Lifetime Mechanical Warranty
- Limited Lifetime Finish Warranty
- Limited Lifetime PVD Finish on Exterior Polished Brass

## Standard Collection Features

- Tubular design
- Weslock Keyway
- 5-pin cylinder
- 1" throw deadbolt with two hardened steel rollers - prevents sawing
- Smooth interior nolin plates
- Panic-Proof— one turn of the interior knob/lever unlocks and opens the door

## Standard Collection Specifications

- Non-adjustable latches 2-3/8" or 2-3/4" with removable faceplates
- Fits doors prepared with 2-1/8" top and 2-1/8" bottom cross holes & 1" edge hole
- Adjusts to door thickness form 1 3/4" to 2-1/4"
- 2-7/8" center to center cross hole spacing

### 1400 Series

- Features 2-point locking mechanism
- Solid brass exterior
- Available with any interior Traditionale Collection knob (except Ball) and lever
- Optional Schlage keyway
- Turn button locking in knob/lever

### 1500 Series

- Available with any interior Traditionale Collection knob or lever style
- Optional Schlage or Kwikset keyway
- 1510/1520
- -2-3/8" center to center edge hole spacing



COLONIAL™  
(1400 SERIES)



LEXINGTON™  
(1400 SERIES)



WOODWARD  
(1400 SERIES)



(Exterior) (Interior)

UNIGARD  
PREMIERE



(Exterior) (Interior)

UNIGARD  
WOODWARD

## Finishes

Style	A	B	D	N	1
Colonial 1400 Series Entry Handle	•				
Lexington 1400 Series Entry Handle	•	•		•	•
Unigard 1500 Series Premiere	•	•	•	•	
Unigard 1500 Series Woodward				•	•
Woodward 1400 Series Entry Handle				•	•
    					
Antique Brass (A)   PVD (B)   Satin Chrome (D)   Satin Nickel (N)   Oil Rubbed Bronze (1)					

# U.L. 60 Minutes Rated



(Interior)

(Exterior)

1824



(Interior)

(Exterior)

1844

## Entry Handles / Unigard

- 5-pin Weslock keyway
- Panic-Proof – one turn of the interior knob/lever unlocks and opens the door
- Combo latch includes:
  - 1" throw with two hardened steel rollers prevent sawing
  - Solid brass spring latch bolt
  - Heavy duty brass fixed faceplate
- Solid brass ASA strikes
- Smooth interior Nolan plate
- ADA compliant

## Specifications

- Fits 2-7/8" center to center cross hole
- Fits 2-3/8" center to center edge hole
- Non-adjustable latches, must specify 2-3/8" or 2-3/4"
- Entry Handles
  - Available with any Traditionale knob (except Ball) or lever style
- Unigard
  - Available with any Traditionale knob or lever style



(Exterior)

(Interior)

8510 UNIGARD™



(Exterior) (Interior)

8520 UNIGARD™  
WOODWARD



867 DEADBOLT



871 DEADBOLT

## Deadbolts

- Exceeds Grade II ANSI A156.2
- 1" throw with two hardened steel rollers prevent sawing
- Solid brass faceplate and no-lip strikes
- Internal metal cups for additional latch fire protection
- Solid brass ADA recommended, extra large interior thumbturn
- 5-pin Weslock keyway
- Rotation collar and 1/4" through bolts
- Wood and metal door screws

## Specifications

- Non-adjustable latches, must specify 2-3/8" or 2-3/4"
- Adjusts to door thickness from 1-3/8" – 2"
- Fits door prepared with 2-1/8" cross hole

### Knob & Lever Features

- Exceeds Grade 3 lock standards
- Solid brass 5-pin cylinder
- Turn button locking in knob/lever
- Solid brass adjustable latch 2-3/8" or 2-3/4" bolt with heavy duty brass fixed faceplates (square or radius)
- Solid brass T-strike (square or radius) with 3" screws
- Weslock keyway
- Internal metal cup for additional latch fire protection

### Specifications

- Adjusts to door thickness from 1-3/8" to 2"
- Fits door prepared with 2-1/8" cross hole and 1" edge hole
- Wood and metal door screws

### Knob & Lever Warranty

- Limited 10 year Mechanical Warranty
- Limited 5 year Finish Warranty



HUDSON



SALEM



BRISTOL



SOMERSET

### Finishes

Style	A	B	D	N	1
Knobs/Levers	•	•	•	•	•
Deadbolts	•	•	•	•	•
1824 Woodward Entry Handle				•	•
1844 Lexington Entry Handle	•		•	•	•
8510 Premiere Unigard	•		•	•	
8520 Woodward Unigard				•	•
					
Antique Brass (A)	PVD (B)	Satin Chrome (D)	Satin Nickel (N)	Oil Rubbed Bronze (1)	



World Headquarters • 8301 East 81st Street, Suite A • Tulsa, Oklahoma 74133

[WWW.WESLOCK.COM](http://WWW.WESLOCK.COM)